

# H<sub>2</sub>OCEAN

## PREMIUM

### WATER MAKER

#### REVERSE OSMOSIS WATERMAKER

If required H2Ocean Watermaker can be easily disassemble for modular installation

Corrosion resistant compact stainless steel frame and components.

Latest generation reverse osmosis  Chemical Membranes

The most efficient and easy operable system

Auto priming function

Designer for 24 hours constant operation

Capable of producing up to 6000 liters per day

Two stage  pre filter ( 5M-25M)

Stainless steel low pressure pump

UV fitter as a standart equipment

Remote control as a Standard equipment

Membrane protection system against sudden pressure increase

High pressure pump protection system against insufficient water flow

2 year warranty



 Certificated

Fresh Water Production

#### MODEL

**pHS90**

**pHS120**

**pHL120**

**pHL180**

**pHL240**

Liter / Hour

90,00

120,00

120,00

180,00

240,00

US Gallons / Hour

23,80

31,70

31,70

47,55

63,40

Liter / Day

2160

2880

2880

4320

5760

US Gallons / Day

571,4

760,8

760,8

1141,2

1521,6

Power (kW)  
Start / Run

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

Voltage (V)

220

220

220

220

220

Weight (kg)

77

79

81

92

97

Dimensions (cm)  
l x w x h

100 x 48 x 44

100 x 48 x 44

108 x 48 x 44

108 x 48 x 44

108 x 48 x 44

Sound Level / 1 m

55

55

53

50

50

Technical Data

# H<sub>2</sub>OCEAN

## ECO WATERMAKER

### REVERSE OSMOSIS WATERMAKER

If required H2Ocean Watermaker can be easily disassemble for modular installation

24 hours production capacity with the most efficient and easy portable system

316-L Stainless steel membrane cover

Long-lasting thermoplastic frame

Two stage  pre filter ( 5M-25M)

Constant product water quality control capability

Membrane protection system against sudden pressure increase

The latest generation reverse osmosis  Chemical Membranes

High pressure pump protection system against insufficient water flow

Optional Features: Auto priming, UV Sterilizer and Remote control panel

1 year warranty



 Certificated

*Optional Features;  
Auto Flushing, UV Sterilizer, Remote Control Panel*

Fresh Water Production

### MODEL

**eHS90**

**eHS120**

**eHL120**

**eHL180**

**eHL240**

Liter / Hour

90,00

120,00

120,00

180,00

240,00

US Gallons / Hour

23,80

31,70

31,70

47,55

63,40

Liter / Day

2160

2880

2880

4320

5760

US Gallons / Day

571,4

760,8

760,8

1141,2

1521,6

Power (kW)  
Start / Run

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

2,2 / 2,0

Voltage (V)

220

220

220

220

220

Weight (kg)

73

75

77

82

92

Dimensions (cm)  
l x w x h

100 x 48 x 44

100 x 48 x 44

108 x 48 x 44

108 x 48 x 44

108 x 48 x 44

Sound Level / 1 m

55

55

53

50

50

Technical Data



www.giayachting.com